# 12kN Pile Fixing Kit

#### Use For Anchor Piles And Bracing Piles

- The 12kN Pile Fixing Kit should be installed in accordance with this leaflet.
- All subfloor construction must be in accordance with NZS 3604:2011.
- NZS 3604 requires lines of lateral support to floor joists within 300 mm of bearer or bracing lines, refer to clause 7.12 of the building code.
- Joists deeper than 150 mm require solid nogging over braced or anchor pile.

#### 12kN Pile Fixing Kit **Pack Contents:**



Each set represents 1x 6kN Pile Fixing Kit

- 2 x Nailon Plates 160 mm Long
- 8 x CT160 Cleats (4 Left Side, 4 Right Side)
- 8 x Annular Grooved SS304 Flat Head Nails 4.0 x 90 mm
- 24 x Annular Grooved SS304 Flat Head Nails 3.5 x 45 mm

Recommended 12kN Pile Fixing Layout SS 304 Cleats (8 per file) 3 Nails Into Bearer and Joist 2 x 90 mm SS304 Nails Skew Driven 12 KN 2 x 90 mm SS304 Nails Skew Driven 2 x SS304 Nailon Plates 8 Nails into Bearer and Pile

## 12kN Joint Fixing Schedule

Pile to Bearer	Nailon Plate (2 Per Joint) 1 mm x 100 mm x 160 mm Long 8 x Nails per Plate into Pile 8 x Nails per Plate into Bearer 2 x Annular Nails (1 Per Face) 4.0 x 90 mm	
Joist to Bearer	CT160 Cleats (4 Per Pile) 160 mm long  3 x Nails per Cleat into Joist  3 x Nails per Cleat into Bearer  2 x 4.0 x 90 mm Annular Grooved SS304 Flat head Nails	
Nails	24 x Annular Grooved SS304 Flat Head Nails 3.5 x 45 mm 8 x Annular Grooved SS304 Flat Head Nails 4.0 x 90 mm	

### Durability

The following table provides an easy guide for selecting Milsons product with corrosion resistant finishes that will meet and exceed NZS 3604:2011 Table 4.1. **Milsons 12kN Pile Fixing Kits** are only available in SS304, therefore suitable for all environments listed.

Zone	Fixing Fastening	Environment		Product
All Zones	Nail Plates	Fully enclosed walls, floors and roof spaces	Closed	Zinc Coated Z275
	C-Nails and Bolts			Hot-Dipped Galvanised Steel
	All other structural fixings	Closed		Carbon Steel-Zinc Coated
Zones B and C	All subfloor fastenings	Vented 7000 mm²/m² or Less	Sheltered	Hot Dipped Galvanised Steel
	more than 600 mm above the ground	Vented MORE than 7000 mm²/m²	Exposed	304 Stainless Steel
	All subfloor fastenings within 600 mm of the ground	Sheltered and Exposed		304 Stainless Steel
	All other atmost wal fixings	Sheltered		Hot Dipped Galvanised Steel
	All other structural fixings	Exposed		304 Stainless Steel
Zone D	All structural fixings	Sheltered and Exposed		304 Stainless Steel



Delivering New Zealand's Leading Fastening Experience



20 Kaimanawa St., PO Box 672 Palmerston North, 4414



Call us on **0800 507 444** 





Visit our website milsons.co.nz

The data provided in this document is for general guidance only and should not be solely relied upon when working to stringent specifications. We recommend consulting with qualified experts regarding any technical queries.